

# Yuasa Technical Data Sheet



## Yuasa NP3.2-12FR Industrial VRLA Battery

### Specifications

|  |     |
|--|-----|
| Nominal voltage (V)                                | 12  |
| 20-hr rate capacity to 1.75v per cell at 20°C (Ah) | 3.2 |
| 10-hr rate Capacity to 1.75v per cell at 20°C (Ah) | 2.9 |
| 20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)     | 3.2 |

### Dimensions

|                            |          |
|----------------------------|----------|
| Length (mm)                | 134 (±1) |
| Width (mm)                 | 67 (±1)  |
| Height over terminals (mm) | 64 (±2)  |
| Mass (kg)                  | 1.1      |

### Terminal Type

|  |      |
|--|------|
| FASTON - Quickfit / release (JST where stated) | 4.75 |
|--|------|

### Operating Temperature Range

|                                      |                |
|--------------------------------------|----------------|
| Storage (in fully charged condition) | -20°C to +60°C |
| Charge                               | -15°C to +50°C |
| Discharge                            | -20°C to +60°C |

### Storage

|   |   |
|---|---|
| Capacity loss per month at 20°C (% approx.) | 3 |
|---|---|

### Case Material

|          |               |
|----------|---------------|
| Standard | ABS (UL94:V0) |
|----------|---------------|

### Charge Voltage

|   |             |
|---|-------------|
| Float charge voltage at 20°C (V)/Block                      | 13.65 (±1%) |
| Float charge voltage at 20°C (V)/Cell                       | 2.275 (±1%) |
| Float Chg voltage tmp correction factor from std 20°C (mV)  | -3          |
| Cyclic (or Boost) charge Voltage at 20°C (V)/Block          | 14.5 (±3%)  |
| Cyclic (or Boost) charge Voltage at 20°C (V)/Cell           | 2.42 (±3%)  |
| Cyclic Chg voltage tmp correction factor from std 20°C (mV) | -4          |

### Charge Current

|  |          |
|--|----------|
| Float charge current limit (A)             | No limit |
| Cyclic (or Boost) charge current limit (A) | 0.8      |

### Maximum Discharge Current

|              |    |
|--------------|----|
| 1 second (A) | 96 |
| 1 minute (A) | 32 |

### Impedance


|                        |    |
|------------------------|----|
| Measured at 1 kHz (mΩ) | 50 |
|------------------------|----|

### Design Life & Approvals

|   |              |
|---|--------------|
| EUROBAT Classification: Standard Commercial | 3 to 5 years |
| Yuasa design life at 20°C (yrs)             | up to 5      |



### Layout



### 3rd Party Certifications

ISO9001 - Quality Management Systems



## Safety

### Installation

Can be installed and operated in any orientation except permanently inverted.

### Handles

Batteries must not be suspended by their handles (where fitted).

### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

### Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

